

MAINTENANCE OF TRAFFIC

1. The Contractor shall be responsible for maintaining safe passage of traffic and protection of his work force throughout the project.
2. A maintenance of traffic plan shall be submitted by the Contractor in accordance with Part Six of the MUTCD and the FDOT Design standards. Unless specifically authorized, the Contractor shall maintain at all times at least one way traffic with a minimum of a 10' (ft) wide lane and a posted speed of not more than 25 miles per hour, with appropriate traffic control. Both lanes shall be opened to traffic during non-working hours.
3. Contractor is to check and maintain on a daily basis all signs, flashing lights, striping and other items as required to conform with the maintenance of traffic plan.
4. Work zone traffic control shall adhere strictly to the requirements of FDOT Design Standards, Index Series 600, the MUTCD and any specific instructions of the County. Noncompliance with these standards will serve as just cause for stopping work at no expense to the County.
5. The proposed sequence of operations and specific maintenance of traffic plans shall be reviewed and approved by the County Engineering Division prior to their implementation.
6. All above ground obstructions within the clear zone of temporary or permanent lanes shall be marked and protected in accordance with FDOT Standard Specifications or specific instructions of the County Engineering Division.
7. Temporary lanes shall be stabilized and suitable for all weather conditions.